

HOSE PROTECTION



GEEVEHYDRAULICS B.V.

HYDRAULISCHE SLANGEN & KOMPONENTEN





Spiralguard



Part Number	Inside Diameter (mm)	Wrapping Range (mm)	Hose Internal Diameter (inches)	1-Wire	2-Wire	Multi Spiral	Dash Size	Standard Pack Quantity
9121-012	9	9-13	3/16	Yes	-	-	-3	20
9121-016	13	13-17	1/4	Yes	Yes	No	-4	20
9121-020	16	16-22	1/4 to 3/8	Yes	Yes	No	-4 to -6	20
9121-025	21	22-28	1/2	Yes	Yes	Yes	-8	20
9121-032	27	27-33	5/8 to 3/4	Yes	Yes	Yes	-10 to -12	20
9121-040	33	33-44	1	Yes	Yes	Yes	-16	20
9121-050	44	44-65	1 1/4 to 1 1/2	Yes	Yes	Yes	-20 to -24	20
9121-075	65	65-90	2	Yes	Yes	Yes	-32	20
9121-090	80	80-200	-	-	-	-	-	20

Custom sizes are also available with coil lengths up to 250 metres.

- * High Density Polyethylene
- * Suitable for the protection of most types of hydraulic, pneumatic and industrial hose assemblies across a wide range of industries.
- * High abrasion resistance.
- * Good resistance to UV exposure.
- * Easy to fit - reduces the risk of industrial injury.
- * Operating temperature: -65 degrees C minimum, 90 degrees C max. continuous, 100 degrees C max. intermittent.
- * Proven in arduous conditions.
- * Conveniently coiled and packed in cartons for easy storage.
- * Supplied lengths and colours:
 - * Standard product is packed in 20m coils.
 - * Colour choice, black or yellow in sizes 12-90mm.
 - * When ordering yellow, add 'Y' as suffix to part number, e.g. SGX-75Y
- * How to calculate quantity:
Outside diameter of hose divided by the Inside diameter of Spiral Guard multiplied by the length (m) of hose to be covered.



Geeve Hydraulics B.V.
Gouderakstraat 61 3079 DB Rotterdam
Postbus 9009 3007 AA Rotterdam
Tel. 010 479 15 11 Fax. 010 479 05 11
E-mail: geeve@geeve.com
Internet: www.geeve.com