


## OTX Female branch tee

Triple-Lok® 37° Flare ends / Female NPTF\* thread (SAE J476)

SAE 070427 MS51513

\*Stainless Steel = NPT to prevent galling



Tube O.D.		Thread NPT/NPTF PT	Thread UN/UNF-2A T	D mm	M1 mm	N1 mm	Y1 mm	Weight (steel) g/1 piece	Triple-Lok® Steel	Triple-Lok® Stainless Steel	Triple-Lok® Brass	PN (bar)	
mm	in.											S	SS
6	1/4	1/8-27	7/16-20	4.4	27	17	14	53	<b>4 OTX-S</b>	<b>4 OTX-SS</b>	<b>4 OTX-B</b>	350	350
8	5/16	1/8-27	1/2-20	6	27	17	14	53	<b>5 OTX-S</b>	<b>5 OTX-SS</b>	<b>5 OTX-B</b>	350	350
10	3/8	1/4-18	9/16-18	7.5	32	22	19	98	<b>6 OTX-S</b>	<b>6 OTX-SS</b>	<b>6 OTX-B</b>	350	350
12	1/2	3/8-18	3/4-16	9.9	36	26	22	145	<b>8 OTX-S</b>	<b>8 OTX-SS</b>	<b>8 OTX-B</b>	310	310
14, 15, 16	5/8	1/2-14	7/8-14	12.3	42	32	27	240	<b>10 OTX-S</b>	<b>10 OTX-SS</b>	<b>10 OTX-B</b>	210	210
18, 20	3/4	3/4-14	1 1/16-12	15.5	48	35	33.3	390	<b>12 OTX-S</b>	<b>12 OTX-SS</b>	<b>12 OTX-B</b>	210	210
25	1	1-11.5	1 5/16-12	21.4	55	41	41	745	<b>16 OTX-S</b>	<b>16 OTX-SS</b>	<b>16 OTX-B</b>	125	125
28, 30, 32	1 1/4	1 1/4-11.5	1 5/8-12	27.4	59	43	47.7	930	<b>20 OTX-S</b>	<b>20 OTX-SS</b>		100	100
35, 38	1 1/2	1 1/2-11.5	1 7/8-12	33.3	73	53	64	2255	<b>24 OTX-S</b>	<b>24 OTX-SS</b>		100	100

Order codes shown are part of our current manufacturing programme.

Imperial and metric parts may vary in hexagon dimensions.

$$\frac{\text{PN (bar)}}{10} = \text{PN (MPa)}$$

Pressure ratings – PN shown, apply to Steel and Stainless Steel versions of the product.

For Brass parts reduce pressures by 35 %.

Do not create drawings from these dimensions, they are subject to change and ISO manufacturing allowances.