



03 Male JIC 37° – Rigid Straight


ISO12151-5-S – AGJ



Part Number	Hose I.D.				Thread NPTF	A mm	B mm	H Inch
	DN	Inch	Size	mm				
30382-4-4	6	1/4	-4	6.4	7/16x20	40	21	1/2
30382-6-6	10	3/8	-6	9.5	9/16x18	45	22	5/8
30382-6-6B	10	3/8	-6	9.5	9/16x18	45	22	5/8
30382-8-8B	12	1/2	-8	12.7	3/4x16	52	26	3/4
30382-8-8	12	1/2	-8	12.7	3/4x16	52	26	3/4
30382-12-12B	19	3/4	-12	19.1	1 1/16x12	69	32	1 1/8
30382-12-12	19	3/4	-12	19.1	1 1/16x12	69	32	1 1/8

06/68 Female – JIC 37° SAE 45° Dual Flare Swivel – Straight

ISO12151-5-SWS – DKJ



Part Number	Hose I.D.				Thread NPTF	A mm	B mm	H	
	DN	Inch	Size	mm				mm	Inch
30682-4-4-SM	6	1/4	-4	6.4	7/16x20	40	21	14	
30682-4-4B	6	1/4	-4	6.4	7/16x20	39	19	9/16	
30682-5-4B	6	1/4	-4	6.4	1/2x20	40	21	5/8	
30682-6-4B	6	1/4	-4	6.4	9/16x18	42	22	11/16	
30682-5-6B	10	3/8	-6	9.5	1/2x20	44	21	5/8	
30682-6-6-SM	10	3/8	-6	9.5	9/16x18	45	22	19	
30682-6-6	10	3/8	-6	9.5	9/16x18	46	22	11/16	
30682-6-6B-SM	10	3/8	-6	9.5	9/16x18	45	22	19	
36882-8-6-SM	10	3/8	-6	9.5	3/4x16	48	25	22	
30682-8-6B	10	3/8	-6	9.5	3/4x16	47	24	7/8	
36882-8-8B-SM	12	1/2	-8	12.7	3/4x16	51	25	22	
36882-8-8-SM	12	1/2	-8	12.7	3/4x16	51	25	22	
30682-10-8B	12	1/2	-8	12.7	7/8x14	52	25	1	
30682-10-10-SM	16	5/8	-10	15.9	7/8x14	65	28	27	
30682-10-10B	16	5/8	-10	15.9	7/8x14	62	25	1	
30682-12-12-SM	19	3/4	-12	19.1	1 1/16x12	67	30	32	
30682-12-12B-SM	19	3/4	-12	19.1	1 1/16x12	67	31	32	

Also available in stainless steel. Details can be found in CAT 4400.1/UK

Approved **fitting series** for hose types:

K: without plastic ring; **B:** Brass; **SM:** Metric Hexagon

82 801 804 821FR 830M 831 836 837BM 837PU 838M