


# Steel Plugs

## 0206 Internal Hexagon Head Plug, Male BSPT Thread

Steel



| C      |                            | E1 | E2<br>min | E2<br>max | F  | G    | H  | Kg    |
|--------|----------------------------|----|-----------|-----------|----|------|----|-------|
| R1/8   | <a href="#">0206 10 00</a> | 6  | 3.1       | 4.9       | 5  | 9.7  | 8  | 0.003 |
| R1/4   | <a href="#">0206 13 00</a> | 8  | 4.7       | 7.3       | 6  | 13.2 | 10 | 0.007 |
| R3/8   | <a href="#">0206 17 00</a> | 8  | 5.1       | 7.7       | 8  | 16.7 | 11 | 0.012 |
| R1/2   | <a href="#">0206 21 00</a> | 8  | 6.4       | 10        | 10 | 21   | 13 | 0.023 |
| R3/4   | <a href="#">0206 27 00</a> | 11 | 7.7       | 11.3      | 14 | 26.4 | 17 | 0.048 |
| R1     | <a href="#">0206 34 00</a> | 13 | 8.1       | 12.7      | 17 | 33.2 | 19 | 0.085 |
| R1 1/4 | <a href="#">0206 42 00</a> | 14 | 10.4      | 15        | 22 | 41.9 | 22 | 0.166 |
| R1 1/2 | <a href="#">0206 49 00</a> | 14 | 10.4      | 15        | 24 | 47.8 | 22 | 0.222 |


For BSPT plugs, from 1/2" - 1 1/2" inclusive

Conforms to DIN 906

Thread, conforms to EN 10226-1

## 0206 Internal Hexagon Head Plug, Male NPT Thread


Steel



| C       |                            | E1 | E2<br>min | E2<br>max | F  | G    | H  | Kg    |
|---------|----------------------------|----|-----------|-----------|----|------|----|-------|
| NPT1/16 | <a href="#">0206 08 00</a> | 6  | 3.8       | 6.4       | 4  | 7.8  | 7  | 0.002 |
| NPT1/8  | <a href="#">0206 11 00</a> | 6  | 3.2       | 5         | 5  | 10.2 | 8  | 0.003 |
| NPT1/4  | <a href="#">0206 14 00</a> | 8  | 4.4       | 7.2       | 6  | 13.6 | 10 | 0.007 |
| NPT3/8  | <a href="#">0206 18 00</a> | 8  | 4.7       | 7.5       | 8  | 17   | 11 | 0.012 |
| NPT1/2  | <a href="#">0206 22 00</a> | 8  | 6.3       | 9.9       | 10 | 21.2 | 13 | 0.023 |
| NPT3/4  | <a href="#">0206 28 00</a> | 11 | 6.8       | 10.4      | 14 | 26.6 | 17 | 0.048 |
| NPT1    | <a href="#">0206 35 00</a> | 13 | 8         | 12.4      | 17 | 33.2 | 19 | 0.082 |

## 0210 Hex Head Plug, Male BSPP and Metric Thread

Steel



| C        |                            | E  | F  | G  | H  | Kg    |
|----------|----------------------------|----|----|----|----|-------|
| M8x1.25  | <a href="#">0210 57 00</a> | 8  | 14 | 12 | 15 | 0.011 |
| M10x1    | <a href="#">0210 60 00</a> | 8  | 14 | 14 | 15 | 0.013 |
| M12x1.25 | <a href="#">0210 66 00</a> | 11 | 17 | 17 | 18 | 0.021 |
| G1/8     | <a href="#">0210 10 00</a> | 8  | 14 | 14 | 15 | 0.013 |
| M14x1.25 | <a href="#">0210 70 00</a> | 11 | 19 | 19 | 20 | 0.032 |
| G1/4     | <a href="#">0210 13 00</a> | 12 | 19 | 18 | 21 | 0.031 |
| G3/8     | <a href="#">0210 17 00</a> | 12 | 22 | 22 | 21 | 0.046 |
| G1/2     | <a href="#">0210 21 00</a> | 14 | 27 | 26 | 24 | 0.078 |
| G3/4     | <a href="#">0210 27 00</a> | 16 | 32 | 32 | 27 | 0.134 |
| G1       | <a href="#">0210 34 00</a> | 18 | 41 | 39 | 33 | 0.269 |
| G1 1/4   | <a href="#">0210 42 00</a> | 20 | 50 | 49 | 35 | 0.441 |


Profile of head undercut conforms to DIN 3852-1, form D/E

BSPP threads, ISO 228-1

Parallel metric threads, NFE 03-054

## 0216 Hex Head Plug, Male BSPT Thread

Steel



| C    |                            | F  | H  | Kg    |
|------|----------------------------|----|----|-------|
| R1/8 | <a href="#">0216 10 00</a> | 13 | 16 | 0.012 |
| R1/4 | <a href="#">0216 13 00</a> | 17 | 19 | 0.023 |
| R3/8 | <a href="#">0216 17 00</a> | 19 | 21 | 0.038 |
| R1/2 | <a href="#">0216 21 00</a> | 22 | 23 | 0.060 |

BSPT thread conforms to EN 10226-1