

Medium Pressure

10 / 48225-...-... - Female ORFS Swivel - Straight

ISO 12151-1 - SWSA SAE J516 - ORFS



10 Series



48 Series

Order Code 46 Series	Order Code 48 Series	Cross Reference Parker	Hose I.D.				Thread UNF
			DN	Inch	Size	mm	
10225-04-04	48225-04-04	1JC48-4-4	6	1/4	-4	6.4	9/16x18
10225-06-04	48225-06-04	1JC48-6-4	6	1/4	-4	6.4	11/16x16
10225-08-04	48225-08-04	1JC48-8-4	6	1/4	-4	6.4	13/16x16
10225-06-05	48225-06-05	1JC48-6-5	8	5/16	-5	7.9	11/16x16
10225-04-06	48225-04-06	1JC48-4-6	10	3/8	-6	9.5	9/16x18
10225-06-06	48225-06-06	1JC48-6-6	10	3/8	-6	9.5	11/16x16
10225-08-06	48225-08-06	1JC48-8-6	10	3/8	-6	9.5	13/16x16
10225-06-08	48225-06-08	1JC48-6-8	12	1/2	-8	12.7	11/16x16
10225-08-08	48225-08-08	1JC48-8-8	12	1/2	-8	12.7	13/16x16
10225-10-08	48225-10-08	1JC48-10-8	12	1/2	-8	12.7	1x14
10225-12-08	48225-12-08	1JC48-12-8	12	1/2	-8	12.7	1 3/16x12
10225-08-10	48225-08-10	1JC48-8-10	16	5/8	-10	15.9	13/16x16
10225-10-10	48225-10-10	1JC48-10-10	16	5/8	-10	15.9	1x14
10225-12-10	48225-12-10	1JC48-12-10	16	5/8	-10	15.9	1 3/16x12
10225-10-12	48225-10-12	1JC48-10-12	19	3/4	-12	19.1	1x14
10225-12-12	48225-12-12	1JC48-12-12	19	3/4	-12	19.1	1 3/16x12
10225-16-12	48225-16-12	1JC48-16-12	19	3/4	-12	19.1	1 7/16x12
10225-12-16	48225-12-16	1JC48-12-16	25	1	-16	25.4	1 3/16x12
10225-16-16	48225-16-16	1JC48-16-16	25	1	-16	25.4	1 7/16x12
10225-20-16	48225-20-16	1JC48-20-16	25	1	-16	25.4	1 11/16x12
10225-20-20	48225-20-20	1JC48-20-20	31	1 1/4	-20	31.8	1 11/16x12
10225-24-24	48225-24-24	1JC48-24-24	38	1 1/2	-24	38.1	2x12

All couplings are also available in stainless steel, please add RVS behind the order code; example **10225-08-08RVS**

Low Pressure

Medium Pressure

High Pressure

Hose Protection

Machines