

Medium Pressure

10 / 48915-...-... - Female - JIC 37° SAE 45° Dual Flare Swivel - 90° Elbow

ISO 12151-5-SWES - DKJ 90°



10 Series



48 Series

Order Code 10 Series	Order Code 48 Series	Cross Reference Parker	Hose I.D.				Thread UNF
			DN	Inch	Size	mm	
10915-04-04	48915-04-04	13W48-4-4	6	1/4	-4	6.4	7/16x20
10915-05-04	48915-05-04	13W48-5-4	6	1/4	-4	6.4	1/2x20
10915-06-04	48915-06-04	13948-6-4	6	1/4	-4	6.4	9/16x18
10915-05-05	48915-05-05	13W48-5-5	8	5/16	-5	7.9	1/2x20
10915-06-05	48915-06-05	13948-6-5	8	5/16	-5	7.9	9/16x18
10915-04-06	48915-04-06	13W48-4-6	10	3/8	-6	9.5	7/16x20
10915-06-06	48915-06-06	13948-6-6	10	3/8	-6	9.5	9/16x18
10915-08-06	48915-08-06	13W48-8-6	10	3/8	-6	9.5	3/4x16
10915-10-06	48915-10-06	13W48-10-6	10	3/8	-6	9.5	7/8x14
10915-06-08	48915-06-08	13948-6-8	12	1/2	-8	12.7	9/16x18
10915-08-08	48915-08-08	13W48-8-8	12	1/2	-8	12.7	3/4x16
10915-10-08	48915-10-08	13W48-10-8	12	1/2	-8	12.7	7/8x14
10915-10-10	48915-10-10	13W48-10-10	16	5/8	-10	15.9	7/8x14
10915-12-10	48915-12-10	13948-12-10	16	5/8	-10	15.9	1 1/16x12
10915-12-12	48915-12-12	13948-12-12	19	3/4	-12	19.1	1 1/16x12
10915-14-12	48915-14-12	13948-14-12	19	3/4	-12	19.1	1 3/16x12
10915-16-12	48915-16-12	13948-16-12	19	3/4	-12	19.1	1 5/16x12
10915-12-16	48915-12-16	13948-12-16	25	1	-16	25.4	1 1/16x12
10915-16-16	48915-16-16	13948-16-16	25	1	-16	25.4	1 5/16x12
10915-20-16	48915-20-16	13948-20-16	25	1	-16	25.4	1 5/8x12
10915-20-20	48915-20-20	13948-20-20	31	1 1/4	-20	31.8	1 5/8x12
10915-24-24	48915-24-24	13948-24-24	38	1 1/2	-24	38.1	1 7/8x12
10915-32-32	48915-32-32	13948-32-32	51	2	-32	50.8	2 1/2x12

All couplings are also available in stainless steel, please add RVS behind the order code; example 10915-08-08RVS