

10 / 48917-...-... - ISO 6162-1 Flange 90° Elbow

ISO 12151-3 - E- L - SFL 90° (21.0 MPa/ 3000 psi)



10 Series



48 Series

Order Code 10 Series	Order Code 48 Series	Cross Reference Parker	Hose I.D.				Flange Inch	Ø mm
			DN	Inch	Size	mm		
10917-08-08	48917-08-08	11948-8-8	12	1/2	-8	12.7	1/2	30
10917-12-08	48917-12-08	11948-12-8	12	1/2	-8	12.7	3/4	38
10917-12-10	48917-12-10	11948-12-10	16	5/8	-10	15.9	3/4	38
10917-12-12	48917-12-12	11948-12-12	19	3/4	-12	19.1	3/4	38
10917-16-12	48917-16-12	11948-16-12	19	3/4	-12	19.1	1	45
10917-20-12	48917-20-12	11948-20-12	19	3/4	-12	19.1	1 1/4	51
10917-12-16	48917-12-16	11948-12-16	25	1	-16	25.4	3/4	38
10917-16-16	48917-16-16	11948-16-16	25	1	-16	25.4	1	45
10917-20-16	48917-20-16	11948-20-16	25	1	-16	25.4	1 1/4	51
10917-24-16	48917-24-16	11948-24-16	25	1	-16	25.4	1 1/2	60
10917-16-20	48917-16-20	11948-16-20	31	1 1/4	-20	31.8	1	45
10917-20-20	48917-20-20	11948-20-20	31	1 1/4	-20	31.8	1 1/4	51
10917-24-20	48917-24-20	11948-24-20	31	1 1/4	-20	31.8	1 1/2	60
10917-32-20	48917-32-20	11948-32-20	31	1 1/4	-20	31.8	2	71
10917-24-24	48917-24-24	11948-24-24	38	1 1/2	-24	38.1	1 1/2	60
10917-32-24	48917-32-24	11948-32-24	38	1 1/2	-24	38.1	2	71
10917-24-32	48917-24-32	11948-24-32	51	2	-32	50.8	1 1/2	60
10917-32-32	48917-32-32	11948-32-32	51	2	-32	50.8	2	71
10917-40-32			51	2	-32	50.8	2 1/2	84
10917-40-40			63	2 1/2	-40	63.5	2 1/2	84
10917-48-48			76	3	-48	76.2	3	102

All couplings are also available in stainless steel, please add RVS behind the order code; example **10917-08-08RVS**

Low Pressure

Medium Pressure

High Pressure

Hose Protection

Machines