


Stud Fittings

3800/3900 One-Piece Cartridge

Stainless steel 316L, FKM



ØD			G	G1	H	H1	H2	N	Kg
4	3800 04 00	3900 04 00	9.8	8	17	8.5	8.5	11	0.006
6	3800 06 00	3900 06 00	12.1	10	19	10.5	8.5	13.5	0.008
8	3800 08 00	3900 08 00	14.8	13	21	12.5	8.5	16	0.012
10	3800 10 00	3900 10 00	17.5	15	24.5	14	10.5	20	0.019
12	3800 12 00	3900 12 00	20	17	25	14.5	10.5	22.5	0.022


3800: collet in stainless steel 303

3900: collet in stainless steel 316L

Cavity dimensions are available in chapter 2.

3809/3909 Stud Elbow, Male BSPT Thread

Stainless steel 316L, FKM




ØD	C			F	G	H	L	Kg
4	R1/8	3809 04 10	3909 04 10	10	10	23.5	16.5	0.020
6	R1/8	3809 06 10	3909 06 10	13	12	27.5	20	0.031
	R1/4	3809 06 13	3909 06 13	14	12	27.5	25	0.036
8	R1/8	3809 08 10	3909 08 10	14	15	32	25	0.040
	R1/4	3809 08 13	3909 08 13	14	14.5	34	25	0.045
10	R1/4	3809 10 13	3909 10 13	19	17.5	37.5	27.5	0.069
	R3/8	3809 10 17	3909 10 17	19	17.5	37.5	27.5	0.070

The body swivels for positioning purposes.

3809 Stud Elbow, Male NPT Thread

Stainless steel 316L, FKM




ØD	C			F	G	H	L	Kg
4	NPT1/8	3809 04 11		11	10	25.5	18.5	0.021
6	NPT1/8	3809 06 11		13	12.5	29	22.5	0.031
	NPT1/4	3809 06 14		14	12.5	29	22.5	0.036
8	NPT1/8	3809 08 11		14	15	34	24	0.040
	NPT1/4	3809 08 14		14	15	34	24	0.045
10	NPT1/4	3809 10 14		19	17.5	39.5	30	0.068
	NPT3/8	3809 10 18		19	17.5	39.5	30	0.071

The body swivels for positioning purposes.

3899/3999 Stud Elbow, Male BSPP and Metric Thread

Stainless steel 316L, FKM




ØD	C			F	G	H	L	Kg
	M5x0.8	3899 04 19	3999 04 19	10	10	26	18	0.020
4	G1/8	3899 04 10	3999 04 10	13	10	27	19	0.022
	G1/4	3899 04 13	3999 04 13	17	10	27	19	0.018
	M5x0.8	3899 06 19	3999 06 19	13	12	33	24	0.031
6	G1/8	3899 06 10	3999 06 10	6	12	33	24	0.031
	G1/4	3899 06 13	3999 06 13	17	12	32	24	0.036
	G1/8	3899 08 10	3999 08 10	14	15	35	25	0.039
8	G1/4	3899 08 13	3999 08 13	17	15	35	25	0.044
	G3/8	3899 08 17	3999 08 17	21	15	34.5	25	0.049
10	G1/4	3899 10 13	3999 10 13	19	17	43	31	0.067
	G3/8	3899 10 17	3999 10 17	21	17	42	31	0.072

The body swivels for positioning purposes.

Stud standpipe 3821, 3921, 3831, 3931 can be used as illustrated, allowing:

- stock optimisation
- installation of tees and elbows where required



LF 3800/LF 3900