



Inwendig:	PVC	Innen:	PVC	Inside:	PVC
Kleur:	Transparant	Farbe:	Transparent	Colour:	Translucent
Uitwendig:	PVC	Aussen:	PVC	Outside:	PVC
Kleur:	Transparant	Farbe:	Transparent	Colour:	Translucent
Topkwaliteit transparante 3 lagen PVC slang met polyester inlagen		Spitzenqualität 3 Lagen transparenter PVC Schlauch mit Polyestereinlagen		Top grade 3 ply transparent PVC hose with polyester reinforcements	
- geschikt voor perslucht, industriële gassen en chemicaliën		- geeignet für Pressluft, Wasser, Industriegase, Chemikalien		- suitable for air, water, chemicals and industrial gases	
- zeer soepel en knikvast, lichte uitvoering		- sehr geschmeidig und knickfest, leichte Ausführung		- souple and kink resistant, light weight	
- minimaal drukverlies		- minimaler Druckverlust		- minimal pressure friction loss	
- RoHS conform		- RoHS konform		- RoHS compliant	

Artikel Nr Artikel Nr Article Nr	Binnen Innen Inside ø mm	Buiten Aussen Outside ø mm	Buigstr. Biegerad. Bendrad. mm	Vakuum Vakuum Vacuum Bar	Gewicht Gewicht Weight gr/m
20LPC0004000	4.0	8.0	32		50
20LPC0004100	4.0	10.0	32		90
20LPC0006000	6.0	12.0	48		100
20LPC0008000	8.0	14.0	64		130
20LPC0009000	9.0	15.0	72		140
20LPC0010000	10.0	16.0	80		150
20LPC0012000	12.0	19.0	96		220
20LPC0013020	13.0	20.0	104		230
20LPC0016000	16.0	24.0	128		310
20LPC0019000	19.0	27.0	152		350
20LPC0025000	25.0	34.0	200		510
20LPC0030000	30.0	41.0	240		750
20LPC0032000	32.0	42.0	256		710
20LPC0038000	38.0	48.0	304		820
20LPC0050000	50.0	60.0	400		1320

Normen / Standards:
RoHS, ISO 1307

Temperatuurbereik (zie medium)
Temperaturbereich (siehe Medium)
Temperature range (see media)
-15 °C +60 °C

Werkdruk Barstdruk
Betriebsdruck Platzdruck
Working Pressure Burst Pressure
10 - 20 bar 30 - 60 bar

Markering / Markierung / Branding:
PETERCLAIR - S - DIA

Lengten / Längen / Lengths:
50 m