

Medium Pressure

10 / 48218-...-... - ISO 6162-2-Flange Straight

ISO 12151-3-S-S - SFS (42.0 MPa/ 6000 psi)



10 Series



48 Series

Order Code 10 Series	Order Code 48 Series	Cross Reference Parker	Hose I.D.				Flange Inch	Ø mm
			DN	Inch	Size	mm		
10218-08-08	48218-08-08	16A48-8-8	12	1/2	-8	12.7	1/2	32
10218-12-10	48218-12-10	16A48-12-10	16	5/8	-10	15.9	3/4	41
10218-12-12	48218-12-12	16A48-12-12	19	3/4	-12	19.1	3/4	41
10218-12-16	48218-12-16	16A48-12-16	25	1	-16	25.4	3/4	41
10218-16-16	48218-16-16	16A48-16-16	25	1	-16	25.4	1	48
10218-20-20	48218-20-20	16A48-20-20	31	1 1/4	-20	31.8	1 1/4	54
10218-24-24	48218-24-24	16A48-24-24	38	1 1/2	-24	38.1	1 1/2	64
10218-32-32	48218-32-32	16A48-32-32	51	2	-32	50.8	2	79

10 / 48818-...-... - ISO 6162-2-Flange 45° Elbow

ISO 12151-3 - E45-S - SFS 45° (42.0 MPa/ 6000 psi)



10 Series



48 Series

Order Code 10 Series	Order Code 48 Series	Cross Reference Parker	Hose I.D.				Flange Inch	Ø mm
			DN	Inch	Size	mm		
10818-08-08			12	1/2	-8	12.7	1/2	32
10818-12-08			12	1/2	-8	12.7	3/4	41
10818-12-10			16	5/8	-10	15.9	3/4	41
10818-12-12	48818-12-12	16F48-12-12	19	3/4	-12	19.1	3/4	41
10818-16-12			19	3/4	-12	19.1	1	48
10818-16-16	48818-16-16	16F48-16-16	25	1	-16	25.4	1	48
10818-20-16			25	1	-16	25.4	1 1/4	54
10818-20-20	48818-20-20	16F48-20-20	31	1 1/4	-20	31.8	1 1/4	54
10818-24-24	48818-24-24	16F48-24-24	38	1 1/2	-24	38.1	1 1/2	64
10818-32-32	48818-32-32	16F48-32-32	51	2	-32	50.8	2	79

All couplings are also available in stainless steel, please add RVS behind the order code; example 10818-08-08RVS