

10 / 48280-... - Male Metric Light Series - Rigid Straight

ISO 12151-2-S-L - CEL



10 Series



48 Series

Order Code 10 Series	Order Code 48 Series	Cross Reference Parker	Hose I.D.				Thread metric	Tube O.D. mm
			DN	Inch	Size	mm		
10280-12-04	48280-12-04	1D048-6-4	6	1/4	-4	6.4	M12x1.5	6
10280-14-04	48280-14-04	1D048-8-4	6	1/4	-4	6.4	M14x1.5	8
10280-16-04	48280-16-04	1D048-10-4	6	1/4	-4	6.4	M16x1.5	10
10280-18-04	48280-18-04	1D048-12-4	6	1/4	-4	6.4	M18x1.5	12
10280-14-05	48280-14-05	1D048-8-5	8	5/16	-5	7.9	M14x1.5	8
10280-16-05	48280-16-05	1D048-10-5	8	5/16	-5	7.9	M16x1.5	10
10280-18-05	48280-18-05	1D048-12-5	8	5/16	-5	7.9	M18x1.5	12
10280-16-06	48280-16-06	1D048-10-6	10	3/8	-6	9.5	M16x1.5	10
10280-18-06	48280-18-06	1D048-12-6	10	3/8	-6	9.5	M18x1.5	12
10280-22-06	48280-22-06	1D048-15-6	10	3/8	-6	9.5	M22x1.5	15
10280-18-08	48280-18-08	1D048-12-8	12	1/2	-8	12.7	M18x1.5	12
10280-22-08	48280-22-08	1D048-15-8	12	1/2	-8	12.7	M22x1.5	15
10280-26-08	48280-26-08	1D048-18-8	12	1/2	-8	12.7	M26x1.5	18
10280-22-10	48280-22-10	1D048-15-10	16	5/8	-10	15.9	M22x1.5	15
10280-26-10	48280-26-10	1D048-18-10	16	5/8	-10	15.9	M26x1.5	18
10280-26-12	48280-26-12	1D048-18-12	19	3/4	-12	19.1	M26x1.5	18
10280-30-12	48280-30-12	1D048-22-12	19	3/4	-12	19.1	M30x2.0	22
10280-36-12	48280-36-12	1D048-28-12	19	3/4	-12	19.1	M36x2.0	28
10280-36-16	48280-36-16	1D048-28-16	25	1	-16	25.4	M36x2.0	28
10280-45-20	48280-45-20	1D048-35-20	31	1 1/4	-20	31.8	M45x2.0	35
10280-52-24	48280-52-24	1D048-42-24	38	1 1/2	-24	38.1	M52x2.0	42

All couplings are also available in stainless steel, please add RVS behind the order code; example 10280-22-08RVS

Low Pressure

Medium Pressure

High Pressure

Hose Protection

Machines