

9125-... - Pyrojacket®

Pyrojacket® is a hollow sleeve or ribbon covering for cables and hoses. Pyrojacket consists of a high bulk glass fibre pad, and a high-temperature silicon fibre coating.

The coating will withstand continuous exposure to temperatures up to 260°C, to temperatures up to 1093° for 15-20 minutes and to temperatures up to 1649°C for 15-30 seconds.

Pyrojacket sleeves can be directly applied to a cable or hose with the connectors or fittings removed, and are available in several different inside diameters 6-127 millimetres.



- Withstands intermittent flame
- Sheds molten spatter of metals and glass
- Resistant to slag and resin build-up
- Protects against abrasion, solvents and corrosive chemicals
- Protects operators against scorching contacts of metal hoses and pipes
- Easily installed

Order Code	Inside Diameter	
	Inch	mm
9125-06	1/4	6.4
9125-08	5/16	7.9
9125-10	3/8	9.5
9125-11	7/16	11.1
9125-13	1/2	12.7
9125-16	5/8	15.9
9125-19	3/4	19.1
9125-22	7/8	22.2
9125-25	1	25.4
9125-29	1 1/8	28.6
9125-32	1 1/4	31.8
9125-35	1 3/8	34.9
9125-38	1 1/2	38.1
9125-41	1 5/8	41.3
9125-45	1 3/4	44.5
9125-51	2	50.8
9125-57	2 1/4	57.1
9125-64	2 1/2	63.5
9125-70	2 3/4	69.9
9125-76	3	76.2
9125-83	3 1/4	82.6
9125-89	3 1/2	88.9
9125-95	3 3/4	95.3
9125-102	4	101.6