




075 - R8 ANTIABRASION

Thermoplastic hose MSHA approved for high pressure hydraulic applications from 140 to 420 bar (2000 to 6000 psi)



FEATURES

Inner Tube

Polyester elastomer

Reinforcement

One or two braids of aramid fiber

Cover

Polyurethane - black - pinpricked - white inkjet branding

Applications

Construction and agricultural equipment - Forklift trucks -
Articulating and telescopic booms - Aerial platforms - Safety and
rescue equipment - Scissor lifts - Cranes - General hydraulics -
Industrial gases

Features

Aramid reinforcement for high pressure performance - Compact
and lightweight - Bonded construction - Abrasion resistant -
Extremely low change in length - Pin-pricked cover

Description

Meets or exceeds SAE 100R8 - Compact high pressure hose suitable for hydraulic applications with increased resistance to abrasion and very low expansion. For use with petroleum or synthetic or water based hydraulic fluids in hydraulic systems. Suitable for general fluid power transmissions like earthmoving or agricultural machinery or forklifts trucks and other high pressure equipment. Also suitable for many industrial gases (check for compatibility). Approved by MSHA - Mine Safety and Health Administration - number IC-305.

Temperature Range

-40 °C to 100 °C (-40 °F to 212 °F): limited to 70 °C (158 °F) for air and water based fluids

Vacuum Rating

-0,93 bar; -700 mm Hg/-13,5 psi; -27,5 inch Hg

Specifications

SAE 100R8 // EN855-R8 // ISO3949-R8

Part no.	DN	Inches	Dash	ID (mm)	OD (mm)	WP (bar)	BP (bar)	ID (inch)	OD (inch)	WP (psi)	BP (psi)	SF	BR (mm)	BR (inch)	Weight (gr/m)	Weight (lb/ft)	Ferrule standard	Ferrule A316L
0750	DN4	1/8	-2	4.0	8.0	420	1,680	0.157	0.315	6000	24000	4:1	25	0.98	45	0.030	SAB101	SAB801
0751	DN5	3/16	-3	5.0	8.9	350	1,400	0.197	0.350	5000	20000	4:1	30	1.18	52	0.035	SAB111	SAB811
0752	DN6	1/4	-4	6.5	11.5	350	1,400	0.256	0.453	5000	20000	4:1	50	1.97	84	0.056	SAB121	SAB821
0753	DN8	5/16	-5	8.1	13.4	300	1,200	0.319	0.528	4300	17200	4:1	55	2.17	106	0.071	SAB131	SAB831
0754	DN10	3/8	-6	9.7	15.5	280	1,120	0.382	0.610	4000	16000	4:1	60	2.36	136	0.091	SAB141	SAB841
0755	DN12	1/2	-8	13.0	19.9	245	980	0.512	0.783	3500	14000	4:1	80	3.15	208	0.140	SAB151	SAB851
0756	DN16	5/8	-10	16.3	23.4	200	800	0.642	0.921	2900	11600	4:1	125	4.92	251	0.169	SAB161	SAB861
0757	DN20	3/4	-12	19.5	27.1	165	660	0.768	1.067	2300	9200	4:1	150	5.91	323	0.217	SAB171	SAB871
0758	DN25	1	-16	25.9	34.2	140	560	1.020	1.346	2000	8000	4:1	200	7.87	443	0.298	SAB181	SAB881

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.

Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.

Document date: 29/06/2021

www.transferoil.com